

DEPARTMENT OF THE ARMY TECHNICAL MANUAL

OPERATOR'S MANUAL:

**INITIALIZATION AND
OPERATING PROCEDURES**

**GUIDED MISSILE AIR DEFENSE
SYSTEM AN/TSQ-73**

**HEADQUARTERS, DEPARTMENT OF THE ARMY
1 AUGUST 1978**

This copy is a reprint which includes current pages from Changes 1 THROUGH 17.

OPERATOR MANUAL: INITIALIZATION AND OPERATING PROCEDURES

GUIDED MISSILE AIR DEFENSE SYSTEM AN/TSQ-73

Current to Tape Version 34.1

TABLE OF CONTENTS

Chapter	Page
LIST OF ILLUSTRATIONS	iv
LIST OF TABLES	vii
VOLUME 3	
3 SYSTEM INITIALIZATION	3-1
Section I. INTRODUCTION	3-1
3-1. Scope	3-1
3-2. Reporting Equipment Publications Improvements	3-1
Section II. HARDWARE INITIALIZATION	3-3
3-3. General.....	3-3
3-4. Equipment Address Options	3-3
3-5. Establish Shelter Lighting	3-3
3-6. Preliminary Control Settings	3-3
3-7. Power Turn-On	3-3
3-8. Shelter Environmental Modes	3-3
3-9. Equipment Initialization	3-3
Section III. SOFTWARE INITIALIZATION	3-19
3-10. General	3-19
3-11. Control Commands	3-19
3-12. Data Entry Errors	3-19
3-13. Position Entry Formats.....	3-27
3-14. Magnetic Tape Unit Cartridge Removal and Installation	3-27
3-15. ADP Operational Checkout (Boot Load)	3-27
3-15.1. Operational Configurations	3-27
3-15.2. Master Battalion (CC143)	3-28
3-16. Site Initialization and Own Site Relocation	3-28
3-17. Program Data Entry	3-28
3-18. Site-Adapter Tape Generation	3-28
3-19. Tape-to-Tape Copy Function	3-28

TABLE OF CONTENTS-Continued

Chapter		Page
4	OPERATING INSTRUCTIONS	4-1
	Section I. OPERATION UNDER USUAL CONDITIONS	4-1
4-1.	General.....	4-1
4-2.	Test Monitor (TMON) Indications	4-1
4-3.	Monitor Mode Operating Procedures	4-1
4-4.	Tracking Mode	4-1
4-5.	Tactical Mode	4-1
4-6.	Tracking/Tactical Mode	4-1
4-7.	Test Mode.....	4-1
4-7.1.	Automatic SIF Code Validation	4-1
4-8.	Data Link Message Processing	4-1
4-8.1.	Engagement of Jam Strobes	4-98.1
4-8.2.	Operation in EW Environment	4-98.1
4-8.3.	System Faker Operations	4-98.1
	Section II. OPERATION UNDER UNUSUAL CONDITIONS	4-99
4-9.	General.....	4-99
4-10.	Determination of Operational Status	4-99
4-11.	Determination of System Fault Status	4-99
4-12.	Operation Reaction to Fault Condition	4-100
4-13.	One-Minute Reconfiguration	4-100
4-14.	Power Turn-Off	4-100
4-15.	Auxiliary Equipment Failure	4-100.1
4-16.	Operation in Adverse Weather Conditions	4-100.1
4-17.	Operation in CBR Environment	4-100.1
4-18.	Memory Protect Reinitialization	4-100.2
4-19.	Legal Entries.....	4-100.2
	Section III. SYSTEM INTEGRATION CHECKOUT	4-119
4-20.	General.....	4-119
4-21.	ATDL-1 Hawk Fire Unit Integration.....	4-119
4-22.	Deleted	
4-23.	Deleted	
4-23.1.	Deleted	
4-24.	Deleted	
4-25.	Remote Source Data Link Operation Verification	4-119
4-26.	Radar/IFF Operation Verification	4-119
4-27.	Multiple AN/TSQ-73 Alinement Requirements	4-119
	Section IV. OPERATOR DAILY PREVENTIVE MAINTENANCE CHECKS AND SERVICES	4-129
4-28.	General.....	4-129
4-29.	Procedure	4-129
5	MAP GENERATION	5-1
5-1.	General.....	5-1
5-2.	Preparation	5-1

TABLE OF CONTENTS-Continued

Chapter		Page
5-3.	Map Generation Procedure	5-1
6	RAID GENERATION	6-1
	Section I. INTRODUCTION	6-1
6-1.	General.....	6-1
6-2.	Generation Flow Diagrams	6-1
6-3.	Raid Tape Target Limits	6-1
	Section II. GENERATION OF SIMULATED RAIDS	6-2
6-4.	Scripted Raid Tape Generation	6-2
6-5.	Generating a Scripted Track Raid Tape Input	6-2
6-6.	Message Formats for Raid Data Input	6-5
6-7.	Preliminary Equipment Control Settings	6-5
6-8.	Rules Governing Message Inputs	6-5
6-9.	Entering Scripted Data Through KPU	6-10
6-9.1	Listing KPU Input	6-10
6-9.2	Editing KPU Input	6-10
6-10.	Raid Tape Generation Procedure	6-10
6-11.	Console Initiated Raid Tape Generation	6-10
6-12.	Recording Console Initiated Targets	6-14
6-13.	Generating a Raid Tape from Recorded Console Inputs	6-14
6-14.	Live Data Raid Tape Generation.....	6-14
6-15.	Live Data Plus Console Initiated Raid Tape Generation	6-14
6-16.	Live Data Plus Scripted Tracks Raid Tape Generation.....	6-14
6-17.	Simulated ECM, Chaff, and Data Link Message Generation	6-14
6-18.	ECM Generation for Raid Exercises.....	6-14
6-19.	Chaff Generation for Raid Exercises.....	6-14
6-20.	Simulated Data Link Information for Raid Tapes	6-14.1
	Section III. SCRIPTED RAID REFERENCE DATA	6-17
6-21.	General.....	6-17
6-22.	Raid Data.....	6-17
7	SIMULATION OPERATION	7-1
7-1.	Raid Tape Implementation and Online Simulation	7-1
7-2.	Raid Tape Operation.....	7-1
7-3.	Simulation Features	7-1
7-4.	Raid Tape Operation and Online Simulation.	7-2
7-5.	Simulated Exercise Error Printout	7-2
7-6.	Playback of a Recorded Simulated Raid Exercise.....	7-2
8	DATA REDUCTION AND RECORDING	8-1
	Section I. DATA RECORDING	8-1
8-1.	General.....	8-1
8-2.	Data Recording Procedure	8-1

TABLE OF CONTENTS-Continued

Chapter		Page
	Section II. DATA REDUCTION	8-5
8-3.	General.....	8-5
8-4.	DRPP Reports	8-5
8-5.	Data Reduction Procedure	8-5
9	FIELD UTILITIES FUNCTION	9-1
9-1.	General.....	9-1
9-2.	Field Utilities Function Operations.....	9-1
9-3.	Special Messages	9-1
9-4.	Error Printouts.....	9-1
9-5.	Field Utilities Function Procedures.....	9-1
9-6.	Support Commands	9-1
9-7.	Output Format Options	9-8.1
9-8.	Field Utilities Functions.....	9-9
9-9.	Field Utilities Function Uses and Typical Operations.....	9-14
9-10.	Terminate Field Utilities Function.....	9-14

LIST OF ILLUSTRATIONS

VOLUME 3

Figure	Title	Page
3-1.	System Initialization -Flow Chart.....	3-2.1
3-2.	Air Damper Operation	3-10
3-3.	Air Conditioning Operation	3-11
3-4.	Error Message Definition.....	3-20
3-5.	Control Command Entry Procedures.....	3-23
3-6.	Abbreviated CC Definitions	3-25
3-7.	Magnetic Tape Unit Cartridge Installation.....	3-29
3-8.	Magnetic Tape Unit Cartridge Removal	3-31
3-9.	ADP Operational Checkout	3-33
3-10.	Normal Bootstrap Load -Channel 11	3-35
3-11.	Normal Bootstrap Load -Channel 10	3-36
3-11.1.	System Configuration.....	3-36.1
3-11.2.	Activate Master Battalion Data Link	3-36.3
3-12.	Site Initialization Procedure	3-37
3-13.	Program Data Entry	3-41
3-14.	Site Adapted Tape Generation	3-45
3-15.	Tape to Tape Copy	3-47
4-1.	Valid Monitor Mode Controls	4-3
4-2.	Valid Tracking Mode Controls	4-5
4-3.	Valid Tactical Mode Controls	4-7
4-4.	Valid Tracking/Tactical Mode Controls	4-9
4-5.	Valid Test Mode Controls.....	4-11
4-6.	Deleted	
4-7.	Console Alerts	4-15

LIST OF ILLUSTRATIONS

VOLUME 3

Figure	Title	Page
4-8.	Angle Marks and Range Marks Display	4-19
4-9.	Assign Site Non-Transmittable Address and Name	4-21
4-10.	Assign Weapons/Bns	4-22.1
4-10.1	Cancel Secondary Assignment	4-24.1
4-11.	Change Tracking Modes	4-25
4-12.	Clear: Hold Fire and Effective	4-26
4-13.	Console Hooking Procedures-Sequence Hook	4-27
4-14.	Console Hooking Procedures-Number GEOREF and Position Hook	4-29
4-14.1	Console Hooking Procedures-Volumes/Lines	4-30.1
4-15.	Console Hooking Procedures-Dehook	4-31
4-16.	Deleted	
4-17.	Designate Expansion Scale	4-32
4-18.	Designate Fire Units and Fire Unit Data by Battalion	4-33
4-19.	Designate Individual Fire Unit and Associated Data for Display	4-34
4-19.1	Disable/Designate Individual PATRIOT FU Engagement Boundary	4-34.1
4-20.	Designate Maps for Display	4-35
4-21.	Display/Deactivate Compressed Video	4-36
4-22.	Display Selected Fire Units and Fire Unit Data	4-37
4-23.	Display Simulated and Test Tracks	4-38
4-24.	Display Time-To-Go Vectors	4-39
4-25.	Display Velocity Vectors	4-41
4-26.	Drop Item (Tracks, Fire Units, Sites, Jam Strobes)	4-43
4-26.1	Enter ADL Engage Command Processing Mode	4-44.1
4-27.	Enter DDG Fire Unit/Site Data	4-45
4-28.	Enter Fixed Point Site	4-47
4-28.1.	Enter G-Sensitivity	4-48.1
4-29.	Enter ID and IFF Data	4-49
4-30.	Enter Interrogate Mode	4-51
4-31.	Enter Intelligence/EW Processing Modes	4-53
4-32.	Enter Automatic Weapons Assignment Parameters	4-54.3
4-32.1.	Enter PADS Parameters	4-54.5
4-32.2.	Enter Defense Priority/Missile Count Thresholds.....	4-54.9
4-32.3.	Enter Subordinate Priority/Missile Count Thresholds	4-54.13
4-33.	Test Pattern Display	4-55
4-34.	Enter Track Data.....	4-57
4-35.	Deleted	
4-36.	Deleted	
4-36.1.	Establish Console Mode	4-60.1
4-37.	Establish Symbol Display.....	4-61
4-38.	Send Salvo and Terminate Commands (Hold Fire, Cease Fire/Engagement)	4-63
4-38.1.	Deleted	
4-39.	Interrogate a Target or Sector	4-65
4-40.	Jam Strobe-Enter Non-ESM Jam Strobe	4-67
4-41.	Manually Initiate a Track	4-68
4-42.	Manually Update a Track	4-69
4-43.	Q73 Remote Radar Selections	4-71
4-44.	Select and Designate Display Offset	4-73
4-45	Select Auxiliary Read Out Data	4-75

LIST OF ILLUSTRATIONS

VOLUME 3

Figure	Title	Page
4-45.1.	Display Data Link Transmission Zone Information on PPI and in ARO	4-76.1
4-46.	Set Console Filters.....	4-77
4-47.	Deleted	
4-48.	Video Selections Procedures	4-81
4-49.	Receive Force Tell, Emergency Tell, and Special Processing	4-83
4-50.	Receive Commands	4-84.1
4-51.	Deleted	
4-52.	Send Action/Management Message	4-87
4-52.1.	Send Command Message	4-88.1
4-53.	Send Operational Status Command Message	4-89
4-54.	Send/Drop Pointer	4-91
4-55.	System Status Messages/Emergency Reconfiguration	4-93
4-55.1.	Jam Strobe Display for Two Fire-Section Battery	4-98.2
4-55.2.	Select and Designate Video Channel Inputs and Outputs	4-98.3
4-55.3.	Designate Manual Clutter Areas	4-98.5
4-55.4.	Delete Manual Clutter Areas	4-98.7
4-55.5.	System Faker Operations	4-98.9
4-56.	System Status Messages-Format and Field Definition	4-100.3
4-57.	Voice Comm Station Failure	4-107
4-58.	KPU Failure	4-109
4-59.	Memory Protect Reinitialization.....	4-111
4-60.	Deleted	
4-60.1.	Deleted	
4-61.	Deleted	
4-61.1.	ATDL-1 Fire Unit Integration with Hawk Battery	4-123
4-61.2.	ATDL-1 Fire Unit Integration with AFU Platoon	4-126.5
4-61.3	Deleted	
4-62.	Deleted	
4-63.	Remote Sources Data Link Operation Verification	4-127
4-64.	Radar/IFF Operation Verification	4-128.1
5-1.	Map Generation	5-2
5-2.	GEOREF Map Example.....	5-2
5-3.	Geographic Map Example	5-2
5-4.	Map Generation Fixed Point Symbols.....	5-3
5-5.	Map Generation Procedure	5-5
6-1.	Raid Tape Generation.....	6-1
6-2.	Scripted Raid Tape Input Generation Flow Chart	6-3
6-3.	Bomb Release Line Calculation and Formula	6-4
6-4.	Sample Overlay Target Characteristics Data	6-4
6-5.	Sample Track Characteristics Matrix	6-5
6-6.	Sample Speed Ruler	6-5
6-7.	Raid Generation Procedure	6-10.1
6-8.	Console Initiated Raid Tape Input Flow Chart	6-15
6-9.	Chaff and ECM Available for Simulation Exercise	6-16
6-10.	Raid Generation Overlays	6-19
6-11.	MAINRAID Program Data	6-25
7-1.	Simulation Equipment Interface	7-1
7-2.	Raid Tape Operation and Online Simulation	7-3

LIST OF ILLUSTRATIONS

VOLUME 3

Figure	Title	Page
7-3.	Simulation Playback	7-7
7-4.	Simulation Playback Procedure	7-9
8-1.	Raid Tape Exercise with Data Recording	8-1
8-2.	Data Recording	8-2
8-3.	Data Recording Procedure	8-3
8-4.	Data Reduction	8-6
8-5.	DRPP Report Index	8-14
8-6.	Data Reduction Option Messages	8-15
8-7.	Data Reduction Error Messages	8-16
8-8.	Deleted	
8-9.	Initialization and System Status Report (Battalion)	8-21
8-10.	Deleted	
8-11.	Initialization and System Status Report (Brigade)	8-33
8-12.	Weapon System Summary Report (Stereo)	8-35
8-12.1.	Weapon System Summary Report (GEOREF)	8-36.1
8-13.	Hostile Track Summary Report	8-37
8-14.	Sequence Event Report (Stereo)	8-38
8-14.1	Sequence Event Report (GEOREF)	8-40
8-15.	Track History Report (Stereo)	8-40.2
8-15.1	Track History Report (GEOREF)	8-42
8-16.	Track Assignment Report	8-42.2
8-17.	Raid Summary Report	8-43
8-18.	Flight Reference Report	8-44
8-19.	DRPP Procedure	8-47
9-1.	Field Utilities Function Preparation	9-6.1
9-2.	Alpha Output Format	9-8.1
9-3.	Formatted Alpha Output Format	9-8.1
9-4.	Hexadecimal Output Options	9-9
9-5.	Typical Tape Format and Layout	9-10
9-6.	Match Operation Output Options	9-13
9-7.	Card Image Tape Generation	9-15
9-8.	Alter Card Image Tape Operation	9-17
9-9.	Map Transfer Operation	9-19

LIST OF TABLES

VOLUME 3

Table	Title	Page
3-1.	Equipment Address Options	3-4
3-2.	Establish Shelter Lighting	3-4
3-3.	Preliminary Control Settings	3-5
3-4.	Power Turn-On Settings	3-8
3-5.	Equipment Initialization Switch Settings	3-13
3-6.	Data Link Switch Settings-Battalion	3-17
3-6.1.	Data Link Switch Settings-Master Battalion	3-17
3-7.	Data Link Switch Settings-Brigade	3-17
3-8.	Modem/Device/Connector Assignments	3-17

LIST OF TABLES

VOLUME 3

Figure	Title	Page
3-9.	Operational Configuration Definitions	3-39
3-9.1.	Auxiliary Functions Available in Configurations	3-40
4-1.	System TMON and Logical Device Numbers	4-102
4-2.	Operational Configuration Definitions	4-105
4-3.	AN/TSQ-73 Legal Entries	4-113
4-3.1.	Deleted	
4-3.2.	Initial Switch Settings at ATDL-1 Hawk Battery for FU Integration	4-121
4-3.3.	Initial Switch Settings at ATDL-1 Hawk AFU Platoon for FU Integration	4-126.3
4-4.	Operator Daily Preventive Maintenance Checks and Services	4-129
6-1.	Begin Target Message	6-6
6-2.	Operational Change Message	6-6
6-3.	ECM Control Message	6-7
6-4.	Chaff Control Message	6-7
6-5.	Data Link Messages	6-8
6-6.	Preliminary Equipment Control Settings	6-10
6-6.1.	Raid Generation Inputs by Use	6-12.3
6-7.	Raid Generation Error Printouts	6-12.5
6-7.1.	Raid Generation Edit Error Messages	6-12.6
7-1.	Simulated Exercise Error Printout	7-2
7-2.	RIE Panel I and II and Simulator Switch Settings for Raid Tape Operation and Online Simulation	7-6.1
8-1.	Display Console Switch and Indicator Codes	8-6
9-1.	Field Utilities Operations Command Formats	9-2.1
9-2.	Field Utilities Special Messages	9-3
9-3.	Field Utilities Error Printouts	9-4

CHAPTER 3

SYSTEM INITIALIZATION

Section I. INTRODUCTION

3-1. Scope. This manual contains the initialization and operating procedures and support program operating procedures for the AN/TSQ-73 System. Before the system becomes operational, system initialization procedures (Chapter 3) must be accomplished. These include hardware setup, power turn-on, optional programming procedures, and radar interface equipment (RIE) alinement. The system initialization flowchart (fig. 3-1) outlines the procedures to be followed when initializing the system. System initialization must be performed in the order shown in the flowchart.


NOTE

Be sure that the procedures described in TM 9-1430-651-12 are completed before attempting procedures in this chapter. After power turn-on, system must warm up for 30 minutes before system becomes fully operational.

3-2. Reporting Equipment Publications Improvements. Reporting of errors, omissions, and recommendations by the individual user for improving this publication is encouraged. Reports should be submitted on DA Form 2028, Recommended Changes to Publications, and forwarded to: Commander, U.S. Army Missile Command, ATTN: AMSMI-MMC-LS-LP, Redstone Arsenal, Alabama 35898-5238. You may also send in your comments electronically to our e-mail address: ls-lp@redstone-emh2.army.mil or by fax 205-842-6546/ DSN 788-6546.

Change 17 3-1/(3-2 blank)

HARDWARE INITIALIZATION



SOFTWARE INITIALIZATION




Figure 3-1. System Initialization - Flow Chart
Change 12 3-2.1/(3-2.2 blank)

Section II. HARDWARE INITIALIZATION

3-3. General. Initialization of system hardware must be accomplished prior to program entries (software initialization) or normal operation. Shelter lighting must be turned on, equipment control settings must be checked before power is applied and, after power is applied, equipment controls must be set to their initial operating states or positions. The tasks described in the following tables and paragraphs must be accomplished in the order given to prevent possible equipment damage. Refer to TM 9-1425-650-12 for physical location of electronic equipment control panels and TM 9-1430-652-10-2 for descriptions of controls and indicators.

3-4. Equipment Address Options. For the purpose of clarity, a specific equipment configuration and selected channel address settings have been assigned for the initialization. However, some major units are interchangeable electrically and functionally and therefore their addresses can be interchanged. Table 3-1 lists those units and the address options available.

3-5. Establish Shelter Lighting. Table 3-2 lists the switch settings necessary to establish shelter lighting in order to accomplish system initialization.

3-6. Preliminary Control Settings. Only the equipment panel controls listed in table 3-3 must be preset before power is applied; all other control positions are irrelevant. In this case, the listed order of the control settings is irrelevant as long as all the controls are set to the listed positions.

3-7. Power Turn-On. Table 3-4 lists the switch settings for applying power to the system electronic equipment.

WARNING

If the modular collective protection equipment (MCPE) is installed but not operating, air baffle 12 (MCPE/AC air intake control) and door of MCPE protective entrance must be open to prevent depletion of oxygen supply.

3-8. Shelter Environmental Modes. The system shelter may be operated in any one of four different environmental modes as determined by setting shelter air baffles, equipment blowers, and MCPE/air conditioner controls as specified in figures 3-2 and 3-3. Available environmental modes are as follows:

a. *Ambient.* In the ambient environmental mode, both equipment and personnel area temperatures are maintained by outside air.

b. *Vent.* In the vent environmental mode, equipment area temperature is maintained by outside air and personnel area temperature is maintained by the air-conditioner (cooling and heating).

CAUTION

Do not change air conditioner modes when the equipment is initialized and operating as power fluctuations will cause memory errors. Wait for an opportune maintenance period, then perform shutdown and restart changing air conditioner modes.

c. *Air-Conditioned.* In the air-conditioned environmental mode, both equipment and personnel area temperatures are maintained by the air-conditioner.

d. *CBR.* The CBR environmental mode is identical to air-conditioned environmental mode except that shelter air is detoxified and the shelter is pressurized by the Modular Collective Protection Equipment (MCPE).

3-9. Equipment Initialization. Tables 3-5 thru 3-7 list the preliminary operating positions of each equipment panel's controls. Any control or indicator not listed in these tables is irrelevant at this point and may be ignored. Set switches in accordance with table 3-5 and table 3-6 or 3-7. Use table 3-6 for modem control settings for battalion configuration operation or table 3-7 for brigade configuration operation. Table 3-8 lists Modem/Device/Connector assignments.

Table 3-1. Equipment Address Options

Unit	Designations	Selection
DDG No. 1	----	Channel 04
DDG No. 2		Channel 06
Computer	Upper and Lower	Primary or Secondary
Tape Units	Upper and Lower	Channel 0(10) or 1(11)
Consoles	Consoles 1 thru 8	Addresses must start with 0 and be consecutive.
Voice Comm Stations	Wall and console	Addresses 1 thru 10
Memories	Memory 1 thru 4	Memory bank addresses are restricted to 0, 1, 2 or 3. One address must be zero: the remainder must be consecutively numbered but can be in any order (i. e, 3, 0, 2, 1). Duplicate addresses are not allowed.
Modems	Memory 5 thru 8 IA/TB	Nonfunctional By addresses assigned during initialization but individual modems must be set for the data link to be used.

¹The basic requirement is that identical equipment may not have more than one unit with the same address (channel) selected and online. For example, either tape unit can be used for any tape unit function if the proper addressing is used.

Table 3-2. Establish Shelter Lighting

Panel	Control	Setting
-------	---------	---------

POWER TRANSFER UNIT

CAUTION

When turning on power for the first time ("cold" start), be sure that all MAIN POWER circuit breakers are off (down position) and all DC power panel circuit breakers, except EMERGENCY POWER BATTERY OUTPUT, UPPER MEMORY RACK NO. 2, and LOWER MEMORY RACK NO.2) are on (up) before external power source is turned on.

When turning on power from a power-loss condition ("re-start"), proceed as above except be sure to keep EMERGENCY OUTPUT circuit breaker in the on (up) position. This permits IBDL backup power to maintain the data in the CMOS memories until main power is established .

NOTE

Be sure external power source is on.

PHASE AVAILABLE	A,B,C on (ind)
PHASE ROTATION	A,B,C on (ind)
POWER SOURCE SELECT	TAC POWER or CONV POWER

MAIN POWER

RELAY COILS SERVICE BREAKER	ON (up)
SYSTEM POWER ON	Green
SHELTER circuit breaker	ON (up)
LIGHTING MAIN	ON (up)
LOCAL LCU/RMT	LOCAL (LCL/RMT if remote display consoles are used)
AUX 5V MONITOR	ON (up)

AC Power Panel

3-4.1/(3-4.2 blank) Deleted

**Table 3-2. Establish Shelter Lighting
- Continued**

Panel	Control	Setting
Single ceiling light assemblies	MAINTENANCE/OPERATIONAL	MAINTENANCE
Dual ceiling light assemblies	MAINTENANCE ON/OFF	ON
Environmental Control Panel	LIGHTING BLKOUT OVERRIDE	ON

NOTE

When AUX 5V MONITOR circuit breaker is set to ON, AC/DC CONVERSION NO. 1 voltage fault UNDER and BATTERY CHRG FAULT indicators may light. Additionally, on the environmental control panel, AIRFLOW FAULT SENSOR DUCT 1 and SENSOR DUCT 2 indicators may light.

Table 3-3. Preliminary Control Settings

Panel	Control	Setting
ADP STATUS AND CONTROL	POWER	
	UPPER CPU	OFF
	LOWER CPU	OFF
	IOU	OFF
	ADP	OFF
	ADP STATUS	
	PRIMARY CPU	
	RUN/INHIBIT	INHIBIT
	SECONDARY CPU	
	RUN/INHIBIT	INHIBIT
	DEVICE CONTROL	
	IOX 1	OFF LINE
	IOX 2	OFF LINE
	IOX 3	OFF LINE
	IOM	OFF LINE
	KEYBOARD PRINTER	OFF LINE
	MEMORY CONTROL	
MEMORY 1		
MEMORY SELECT	OFF	

**Table 3-3. Preliminary Control Settings
- Continued**

Panel	Control	Setting
ADP STATUS AND CONTROL	MEMORY 2	
	MEMORY SELECT	OFF
	MEMORY 3	
	MEMORY SELECT	OFF
	MEMORY 4	
	MEMORY SELECT	OFF
	MEMORY 5	
	MEMORY SELECT	OFF
MEMORY 6		
MEMORY SELECT	OFF	
MEMORY 7		
MEMORY SELECT	OFF	
MEMORY 8		
MEMORY SELECT	OFF	
DATA COMMUNICATION	POWER SUPPLIES	
	LOWER	
	1(CLOCK)	OFF
	2	OFF
	3	OFF
	4	OFF
	UPPER	
	1	OFF
	2	OFF
	3	OFF
	4	OFF
	IBDL	
	ON/OFF	OFF

NOTE

The modem control panels are located in door 2 of rack 2. The indicated control settings are made on all modem control panels.

Modem	POWER ON/OFF	OFF
RADAR SIMULATOR	MODE	OFF LINE
	RCVR NOISE VOLTS PEAK	OFF