TE	\sim 11		\sim	A 1	B 4	A	N.			
	СН	IN	ı	ΑL	. IVI	А	N	ı	JΑ	ıL

LOADING AND STOWAGE

OF MILITARY AMMUNITION

AND EXPLOSIVES ABOARD

BREAKBULK MERCHANT SHIPS

Approved for public release; distribution is unlimited.

TECIHNICAL MANUAL
No. 55-607
NAVY PUBLICATION
NAVSEA OP 3221 REV 2

HEADQUARTERS
DEPARTMENTS OF THE ARMY
AND TIIE NAVY
WASHINGTON, DC, 27 December 1988

LOADING AND STOWAGE OF MILITARY AMMUNITION AND EXPLOSIVES ABOARD BREAKBULK MERCHANT SHIPS

Approved for public release; distribution is unlimited.

CHAPTER	4	INTRODUCTION	Paragrapn	Page
CHAPTER	١.	Purpose and Scope	1_1	1-1
		Report of Publication Improvements	1-2	1-1
		Application and Intended Use	1-3	1-1
		Compliance with Federal Regulations	1-4	1-1
		Compliance by Navy Activities	1-5	1-1
CHAPTER	2.	PERMITS, CERTIFICATIONS, INSPECTIONS, AND ACCEPTANCE		
		General	2-1	2-1
		Permit for Handling Military Explosives		2-1 2-1
		Inspections and Acceptance	2-3 2-4	2-1
		Standard Feedback Forms and Systems	2-5	2-3
CHAPTER	3.	PRELOAD REQUIREMENTS	2 0	
		General	3-1	3-1
		Preloading Inspection	3-2	3-1
		Planning	3-3	3-1
		Cargo Stowage Plan	3-4	3-1
CHAPTRER	1	Estimation of Requirements for Materials and Personnel	3-5	3-7
CHAPIRER	4.	General Loading Procedures	1₋1	4-1
		Types of Stowage		4-6
		Deck Stowage		4-6
		General Types of Explosive Loads	4-4	4-7
		General Stowage Procedures	4-5	4-10
		Use of Power-Operated Industrial Trucks	4-6	4-10
CHAPTER	5.	APPROVED MATERIALS AND SPECIFICATIONS		
		General		5-1
		Wood		5-1 5-2
		PlywoodNails		5-2 5-2
		Stranning Lashing and Tiedown Gear	5-4 5-5	5-2 5-3
		Strapping, Lashing, and Tiedown Gear	5-6	5-3
		Tools	5-7	5-3
CHAPTER	6.	SECURING PROCESS		
		Introduction	6-1	6-1
		Mechanics of Ship Motions		6-1
		Fundamental Securing		6-5
		Preload Securing	6-4	6-9
CHAPTER	7.	General Sawing and Nailing PracticesSTANDARD SECURING STRUCTURES AND REQUIREMENTS	ხ-5	6-17
CHAPTER	1.	General	7 1	7-1
		Decking		7-1 7-1
		Dunnage Flooring		7-1 7-11
		Darmage riceming		, , ,

^{&#}x27;This manual supersedes TM 55-607, NAVSEA OP 3221 Rev 1 September 1976

			Paragraph	
		End BulkheadsPartition Bulkheads		7-12 7-21
		Division Bulkheads		7-23
		Encasement		7-25
		Class A" Magazine Stowage Tomming		7-31 7-37
		Stepping Down a Load		7-37 7-40
		Open-Hold Guardrail	7-11	7-42
		Deck-stow Securing		7-43
CHAPTER	8.	BLOCK-STOW AND SWEATBOARD-TO-SWEATBOARD SECURING TEC		
		General	8-1	8-1
		Block-Stow Technique Block Shoring of Cargo Voids		8-4 8-18
		Sweatboard-to-Sweatboard Stowage Technique	8-4	8-22
		Sweatboard-to-Sweatboard Shoring of Cargo Voids	8-5	8-28
CHAPTER	9.	SECURING OFSPECIFIC LOADS Introduction	0.4	0.4
		Securing of Rectangular Unit Loads	9-1 9-2	9-1 9-1
		Securing of Round, Single-Item Loads	9-3	9-33
		Securing of Overhanging Unit Loads	9-4	9-45
		Securing of Unitized Loads of Containers and Single Containers	9-5	9-90
CHAPTER	10.	BARGE LOADING		
		General	10-1	10-1
		Purpose	10-2 10-3	10-1 10-1
		Characteristics		10-3
		Cargo Stowage	10-5	10-4
		Standard Block and Bracing Requirements		10-12 10-17
		Lighters Preliminary Operations	10-7	10-17
		Dunnage Requirements	10-9	10-19
APPIEND)I		REFERENCESGENERAL PROPERTIES OF DUNNAGE LUMBER		A-1
APPENDIX APPENDIX		TYPES AND CHARACTERISTICS OF COMMON NAILS AND WOOD SCR	EWS	B-1 C-1
APPENDIX	_	SHIP CHARACTERISTICS		D-1
APPENDIX		SHIP'S CARGO-HANDLING GEAR		E-1
GLOSSAR' INDEX	Y			
INDEX			IIIGOX I	
		LIST OF ILLUSTRATIONS		
Figure No.		Title		Page
	1-1 2-1	Military cargo being loaded aboard merchant-type ship		1-2 2-2
	2-2	Report of Discrepancy (ROD) (SF 364) (Sheet 1 of 2)		2-4
	2-2	Report of Discrepancy (ROD) (SF 364) (Sheet 2 of 2)		2-5
	2-3	Transportation Discrepancy Report (SF 361) (Sheet 1 of 2)		2-7
	2-3 2-4	Transportation Discrepancy Report (SF 361) (Sheet 2 of 2)		2-8 2-10
	2-5	Typical ammunition stowage evaluation sheet		2-10
	3-1	Typical preliminary cargo stowage plan for a single hatch		3-3
	3-2	Typical preplan for an entire ship		3-4
	3-3 3-4	Use of compartment diagram during preload planning		3-6 3-8
	3-5	Typical materials estimate sheet		3-10
	3-6	Organization of a typical Civil Service loading force		3-12
	4-1 4-2	Explosives spotted for loading		4-2 4-3
	4-2 4-3	Typical lift of palletized cargo		4-3 4-5
	4-4	Typical palletized unit loads		4-8

Figure No	o. Title	Page	
4-5	Round, single-item load (3,000-pound bombs)	4-9	
4-6	Unit load with overhang (500-pound bombs)	4-9	
4-7	Unitized load for containers (CBU-55/B)	4-10	
6-1	The six basic ship motions	6-1	
6-2	Static forces while ship is underway ill calm seas	6-2	
6-3	Static forces due to roll motion	6-3	
6-4	Dynamic forces due to roll motion	6-4	
6-5	Dynamic forces due to pitch motion	6-5	
6-6	Basic blocking for wood deck	6-6	
6-7	Basic blocking for metal deck	6-7	
6-8 6-9	Basic bracing for wood deck	6-8 6-9	
6-10	Basic bracing for metal deck	6-10	
6-11	Compartment requiring preload cleanup	6-11	
6-12	Hangar sweatboards	6-12	
6-13	Nonheat end bulkhead under construction	6-13	
6-14	Typical completed heat and nonheat bulkheads	6-14	
6-15	Installation of spacer material prior to stowage	6-15	
6-16	Boarding over of obstructions on permanent, bulkhead	6-16	
6-17	Partial encasement	6-17	
6-18	Dockside wood ship	6-18	
6-19	Onboard assembly of prefabricated structures	6-19	
6-20	Direct nailing	6-20	
6-21	Total holding power of multiple nails	6-21	
6-22 6-23	Nail penetration required to resist maximum allowable lateral loads	6-22 6-23	
7-1	Strip decking/flooring	7-2	
7-1 7-2	Construction of wood decking with 1-inch lumber	7-2 7-3	
7-3	Construction of 2-inch wood decking laid athwartships	7-4	
7-4	Void table method for shoring deck obstructions	7-5	
7-5	Construction details for flooring over tank top	7-6	
7-6	Partial elevated flooring	7-7	
7-7	Comparison of flooring over hatch boards with stowage of wood pallets directly on hatch boards	7-8	
7-8	Construction details for flooring over the shaft alley	7-9	
7-9	Construction of tier decking for unit loads with overhang	7-10	
7-10	Construction of tier decking for nose-to-butt bomb stowage	7-11	
7-11	Construction details for heat bulkhead on stiffener side of ship's bulkhead	7-13	
7-12 7-13	Construction details for heat bulkhead with jacks	7-14 7-16	
7-13 7-14	Construction details for nonheat bulkhead on stiffener side of ship's bulkhead	7-10 7-17	
7-1 4 7-15	Construction details for nonheat bulkhead with A-frame	7-17	
7-16	Construction details for nonheat securing structures of bulkheads with deck bracing	7-20	
7-17	Construction details for nonheat securing structures against the shaft alley	7-21	
7-18	Construction details for partition bulkhead	7-22	
7-19	Construction details for division bulkhead	7-24	
7-20	Complete encasement of beams and pipes	7-25	
7-21	Complete encasement of kingpost within class "A" magazine	7-26	
7-22	Partial encasement of ladder and stanchion	7-27	
7-23	Rectangular unit loads emplaced around partially encased ladder and stanchion	7-28	
7-24 7-25	Partial encasement of air vent	7-29 7-30	
7-25 7-26	Construction details for framework of class "A" magazine (nonportable)	7-30 7-32	
7-20 7-27	Construction details for side of class "A" magazine (nonportable)	7-32	
7-28	Class "A" magazine under construction (nonportable)	7-34	
7-29	Construction details for portable class "A" magazine	7-36	
7-30	Installation of barrier material	7-37	
7-31	Construction details for overhead A-frame tomming	7-38	
7-32	Construction details for A-frame tomming under tween-deck hatch beams	7-39	
7-33	Construction details for tomming in square of hatch	7-40	
7-34	Stepping down toward center of compartment	7-41	
7-35	Completion of stow with smaller unit loads	7-42	
7-36	Construction details for open-hold guardrail	7-43	
7-37	Construction details for closed deck-stow structure	7-44	
7-38 7-30	a,pical closed deck-stow structure under construction	7-45 7-46	
7-39 7-40	Construction details for open deck-stow structure	7-46 7-47	
7-40	Special deck stowage of weatherproof containers	7-47	

iii

Figure No	o. Title	Page
8-1	Block stowage	8-2
8-2	Sweatboard-to-sweatboard stowage	8-3
8-3	Stowage nomenclature	8-3
8-4	Fundamental block-stow securing structure	8-5
8-5	Typical block-stow securing (hull blocking technique)	8-6
8-6	Construction details for basic block-stow securing prepared in advance (hull blocking technique)	8-/
8-7	Pre-positioning of dunnage lumber	8-8
8-8 8-9	Emplacement of initial unit loads for block stowage	0-9
8-10	Addition of lacing for block stowage (hull blocking technique)	0-10 2-11
8-11	Installation of flooring support structures (hull blocking technique)	8-12
8-12	Bracing uprights to the hull (hull blocking technique)	8-13
8-13	Installation of lacing (hull blocking technique)	8-14
8-14	Construction of flooring supports (hull blocking technique)	8-15
8-15	Runners for support of flooring (hull blocking technique)	8-16
8-16	Installation of flooring over lower course stripping (hull blocking technique) Resumption of the block-stow pattern (hull blocking technique)	8-17
8-17	Resumption of the block-stow pattern (hull blocking technique)	8-18
8-18	Shoring small voids in the block-stow pattern	8-19
8-19	Final void shoring in progress	8-20
8-20	Construction details for narrow and full-block void shoring structures	8-21
8-21 8-22	Void shoring for unit loads that overhang the pallet	
8-23	Strip sheathing with loads emplaced	o-∠ა 2-24
8-24	One-point technique of unit-load positioning (sweatboard blocking technique)	8-26
8-25	Top tier bracing at sweatboards, small hull angles (sweatboard blocking technique)	8-27
8-26	Top tier bracing at sweatboards, severe hull angles (sweatboard blocking technique)	8-28
8-27	Sweatboard-to-sweatboard stowage of 20-mm cartridges, lower hold No. 1 (sweatboard blocking technique)	8-29
8-28	Construction details for prefabricated void table	8-30
8-29	Full-block structure for tier voids, two-face-board construction	8-31
8-30	Sequential shoring of cargo void (sweatboard blocking technique)	8-32
8-31	Shoring voids at the sweatboards (sweatboard blocking technique)	8-34
8-32	Full-block structure used with 750-pound-bomb unit loads	8-35
8-33	Top tier void in process of being blocked	8-36
8-34 9-1	Full-block structure for narrow-tier voids	8-37
9-1	(sweatboard blocking technique)	0-2
9-2	Sweatboard-to-sweatboard securing of 500-pound fire bomb, BLU-32/B, in lower hold No. 5,	9-2
0 2	C3 hull (sweatboard blocking technique)	9-4
9-3	Stowage of palletized unit loads in tween-deck compartments	9-6
9-4	Strip sheathing and bulkhead requirements for 105-mm unit loads (sweatboard blocking technique)	9-7
9-5	Securing of 105-mm palletized unit loads at the hull (hull blocking technique)	9-8
9-6	Fore-and-aft shoring of palletized boxed ammunition (forward hold 1, afterward view, hull blocking	
	technique)	9-9
9-7	Construction of void shoring and flooring support structure for 105-mm unit loads	9-10
9-8	Alternate method of securing voids in stowage of 105-mm cartridges	9-11
9-9	Construction of a full floor over 105-mm HE cartridges	9-12
9-10 9-11	Stowing and securing of 105-mm HE cartridges, lower hold No. 4, port side of shaft alley	9-13 0 ₋ 14
9-12	Stowing and securing of 20-mm cartridges, lower hold No. 3 (sweatboard blocking technique)	9-14
9-13	Stowing and securing of 20-mm cartridges, deep tank No. 4 (sweatboard blocking technique)	9-18
9-14	Typical prefabricated nonheat bulkhead and securing structures for stowage of 155-mm projectiles,	
	tween-deck compartments	9-20
9-15	Stowage of initial tier of projectiles, tween-deck compartments (sweatboard blocking technique)	9-21
9-16	Filler assembly for offset units	9-22
9-17	Construction details for flooring over projectiles	9-23
9-18	Construction of flooring (decking) over 155-mm projectiles	9-24
9-19	Mixed stowage of 155-mm projectiles with other explosives cargo (stowage in progress)	9-25
9-20	Continuation of block stowage of projectiles in upper tiers	9-26
9-21	Sweatboard-to-sweatboard stowage of 155-mm projectiles, lower hold No. 1 (sweatboard blocking technique)	0.20
9-22	Sweatboard-to-sweatboard stowage of projectiles in compartment with convex sheer	ყ-∠8
3-22	(sweatboard blocking technique)	0_20
9-23	Stowing and securing 155-mm projectiles, lower hold No. 3 (hull blocking technique)	9-30
9-24	Stowing and securing of 155-mm projectiles, shaft alley, deep tank No. 4 (hull blocking technique).	9-31
9-25	Stowing and securing of M4A2 propellant charges in tween-deck compartment	9 - 32
9-26	Stowing and securing of 3.000-pound bomb, tween deck No. 3 (hull blocking technique)	

iv

Figure No	o. Title I	Page
9-27	Stowing and securing of 3,000-pound bomb, lower hold No. 1 (hull blocking technique)	. 9-36
9-28	BLU-82/B 15,000-pound slurry bomb, skidded unit load	
9-29	Preload boarding and flooring for 15,000-pound slurry bomb	. 9-38
9-30	Construction details for nose boarding in nose-to-base stowage	. 9-39
9-31	Stowing and securing of 15,000-pound slurry bomb, nose-to-base, fore-and-aft	. 9-40
9-32	Stowing and securing of 15,000-pound slurry bomb, base-to-base, athwartship	. 9-42
9-33	Stowing and securing of 15,000-pound slurry bomb, nose-to-base, athwartship	. 9-44
9-34	Typical 500-pound bomb, Navy, palletized unit load (metal pallet)	. 9-45
9-35	Typical 500-pound bomb-palletized unit load (wood pallet)	. 9-46
9-36	250-pound-bomb palletized unit load	. 9-47
9-37	1,000-pound-bomb palletized unit load	. 9-47
9-38	2,000-pound-bomb palletized unit load	
9-39	Correct alignment for nose-to-butt stowage of 500-pound bombs	. 9-49
9-40	Stowage of 500-pound-bomb unit loads in rectangular compartments	. 9-50
9-41	Simple block stowage of 500-pound-bomb unit loads, lower bold No. 5 (hull blocking technique)	. 9-51
9-42	Partially completed prefabricated securing for 500-pound-bomb unit loads (hull blocking technique) .	. 9-52
9-43	Nonprefabricated securing installed after loading	. 9-53
9-44	Typical preconstructed shoring for block stowage of 500-pound bombs in lower holds	. 9-54
9-45	Stowing and securing of 500-pound bombs, lower hold No. 3, port cell (hull blocking technique)	. 9-55
9-46	Block stowage by levels, 500-pound-bonib unit loads, lower hold No. 3, starboard cell	
	(hull blocking technique)	. 9-56
9-47	Fore-and-aft restraint of end unit loads (hull blocking technique)	. 9-57
9-48	Construction of support structures for flooring over voids in the wings (hull blocking technique)	. 9-58
9-49	Completion of flooring prior to stowage of additional tiers of bombs (hull blocking technique)	. 9-59
9-50	Stowing and securing of 500-pound bombs in lower holds bisected by shaft alley	
	(sweatboard blocking technique)	. 9-60
9-51	Sweatboard-to-sweatboard stowage of 500-pound bombs, forward lower holds (sweatboard blocking	
	technique)	. 9-62
9-52	Sweatboard-to-sweatboard stowage of 500-pound bombs, aft lower holds (sweatboard blocking technique)	. 9-64
9-53	Stowing and securing of 500-pound bombs, lower hold No. 3, at heat bulkhead (sweatboard blocking	l
	technique)	. 9-66
9-54	Stowing and securing of 500-pound bombs, lower hold No. 3, forward of heat bulkhead (sweatboard blocking	
	technique)	
9-55	Height differential dunnaging for 500-pound-bomb unit loads in the square of the hatch	. 9-68
9-56	Tween-deck stowage of 750-pound-bomb unit loads	
9-57	Block stowage of 750-pound bombs (hull blocking technique)	. 9-71
9-58	Butt-to-butt shoring and shoring of tier voids in block stowage of 750-pound bombs (sweatboard blocking	
	technique)	. 9-73
9-59	Flooring over 750-pound-bomb unit loads	. 9-74
9-60	Basic sweatboard-to-sweatboard stowage of 750-pound bombs, forward lower holds (sweatboard blocking	
	technique)	. 9-76
9-61	Sweatboard-to-sweatboard stowage of 750-pound bombs, aft lower holds (sweatboard blocking technique)	. 9-78
9-62	Stowing and dunnaging of 750-pound bomb, lower hold No. 3 (sweatboard blocking technique)	
9-63	Stowing and dunnaging of 750-pound bomb, deep tank No. 4 (sweatboard blocking technique)	. 9-82
9-64	Typical stowage of 2,000-pound bomb, tween-deck compartments (sweatboard blocking technique)	. 9-84
9-65	Sweatboard-to-sweatboard stowage of 2,000-pound bombs, lower hold No. 5 (sweatboard blocking	
	technique)	. 9-86
9-66	Six reduced-charge powder tank cans (MK 12 MOD 0 pallet)	. 9-87
9-67	Six full-charge powder tank cans (MK 3 MOD 0 pallet)	. 9-88
9-68	Single armor-piercing (AP) projectile (MK 85 MOD 0 handling bands)	. 9-88
9-69	Two high-capacity (HC) projectiles (MK 3 MOD 0 pallet)	. 9-89
9-70	Support of tier decking for 2,000-pound bombs stowed nose-to-nose	. 9-90
9-71	Stowing and securing of CBU-55/B, tween deck No. 3 (sweatboard blocking technique)	
9-72	Block stowage of CBU-55/B in compartment with significant hull curvature (hull blocking technique).	
9-73	Stowing and securing of CBU-25/A single containers in square of hatch	. 9-95
10-1	Completed stow of 500-pound-bomb unit load in a LASH lighter	. 10-2
10-2	Dimensions of a typical LASH lighter	. 10-4
10-3	Preplan for LASH lighter	. 10-5
10-4	Final stowage plan for LASH lighter	
10-5	Basic block-stowage pattern	. 10-7
10-6	Basic staggered block-stow pattern	. 10-8
10-7	Staggered block stow of 1,000-pound-bomb unit loads, MK 83	
10-8	Void shoring for staggered block stowage	. 10-10
10-9	The modified block-stowage pattern	. 10-1
10-10	Construction details for bulkhead jack	. 10-13
10-11	Completed encasement of stacking post	. 10-1

v

Figure No	D. Title	age
10-12 10-13 10-14 10-15 10-16 10-17 10-18 10-19 B-1 D-1 D-2 D-3 D-4 E-1 E-2	Construction details for encasement of ladder/stanchion combination with jacks The step-down technique Use of diagonally braced bulkhead for securing top layer of stow Three types of lighters Top view of a typical YFN lighter Side view of a typical YFN (modified) lighter Sheathing and loading areas Interior of YFN (modified) during loading operations General classifications of softwood lumber VC2 (Victory) hull configuration C2 hull configuration C3 hull configuration C4 hull configuration Typical mast rigging Typical kingpost rigging LIST OF TABLES	10-15 10-16 10-18 10-19 10-20 10-21 B-3 D-3 D-3 D-4 D-4 E-1
Table No.		Page
5-1 B-1 B-2 B-3 C-1 C-2 C-3 C-4 C-5 C-6 D-1 D-2 E-1	Comparison of Approved Construction Techniques with Alternate Methods Properties of Structural Lumber Commonly Used in Dunnaging Commercial Lumber Grading Associations and Publications Grouping of Species for Determining Allowable Loads for Nails and Screws Sizes of Common Wire Nails and Spikes Sizes of Threaded, Hardened Steel-Type Nails Allowable Withdrawal Loads for Nails and Spikes-Normal Duration Allowable Lateral Loads for Nails and Spikes-Normal Duration Allowable Withdrawal Loads for Wood Screws-Normal Duration Allowable Lateral Loads for Wood Screws-Normal Duration Average Characteristics of Principal Types of US Flag Break-bulk Dry Cargo Merchant Ships Characteristics of Typical Commercial Steel LASH Lighters Ship's Cargo-Handling Gear Inspection	5-4 B-1 B-2 B-4 C-1 C-1 C-2 C-4 C-5 C-6 D-2 D-5

CHAPTER 1 INTRODUCTION

1-1. Purpose and Scope

This manual provides an operational reference guide for loading military munitions and explosives aboard breakbulk merchant ships. Only breakbulk stowage methods are discussed. Container loading procedures are described by specific outloading drawings prepared by the Services. The text provides general guidance for military and civilian personnel engaged in loading, blocking, and bracing military explosives cargo for ocean movement by ships in conformance with the Code of Federal Regulations (CFR), Title 46, Part 146 (46 CFR146).

1-2. Report of Publication Improvements

Users of this publication are encouraged to recommend changes and submit comments for its improvement. Comments should be keyed to the specific page, paragraph, and line of the text in which the change is recommended. Reasons will be provided for each comment, to ensure understanding and complete evaluation. Comments should be prepared on DA Form 2028 (Recommended Changes to Publications and Blank Forms) or in a letter and forwarded to the Commander, Military Traffic Management Command, ATTN: MT-SA, 5611 Columbia Pike, Falls Church, VA 22041-5050, or the Commander, Naval Weapons Station Earle, ATTN: Naval Weapons Handling Laboratory, Colts Neck, New Jersey 07722. All proposed changes will be evaluated and approved by both commands.

1-3. Application and Intended Use

The information in this publication is intended for personnel, at shiploading activities, who are concerned with loading and shoring military explosives onboard merchant ships. Particular emphasis is placed on dunnaging, with text and illustrations directed to the requirements of blockers and bracers. Additional information concerning associated functions, such as cargo planning, equipment and material scheduling, inspection, and labor requirements, is sufficiently detailed to describe the complete environment of shiploading and cargo stowage. When used in conjunction with applicable Federal and military regulations, this manual will provide ammunition terminals with a synopsis of user-tested procedures for the safe securing of breakbulk ammunition and explosives. Shiploading drawings, as listed in the Department of the Army Pamphlet 310-24, are available for the stowage and shoring of US Army guided missile and large rocket components in accordance with approved methods and procedures. References are contained in appendix A

1-4. Compliance With Federal Regulations

Procedures in this manual comply with requirements established in 46CFR146-29. These regulations prescribe the responsibilities of shippers and carriers of military explosives and hazardous materials and provide for their enforcement. Figure 1-1 shows a typical merchant ship being loaded with military ammunition and explosives.

1-5. Compliance by Navy Activities

Navy activities are required by OPNAV 8023.22A to comply with OP 3221/TM 55-607.




Figure 1-1 Military cargo being loaded aboard merchant-type ship. 1-2

CHAPTER 2 PERMITS, CERTIFICATES, INSPECTIONS, AND ACCEPTANCE

2-1. General

The hazardous properties of military explosives cargo require strict compliance with the accepted standards for packaging, marking, loading, and securing of dangerous cargoes. This chapter provides a summary of procedures for certification, inspections, and acceptance as required by 46CFR146 and local regulations.

2-2. Permit for Handling Military Explosives

Authorization to load, handle, or discharge military explosives and lethal chemicals, except Coast Guard Class I, on any vessel at a United States port must be obtained from the District Commander of the US Coast Guard, Captain of the Port, or other officer designated by the District Commander. Specific policies concerning permits for handling military explosives are defined by 46CFR146.29-13(a) and (b).

2-3. Certification of Cargo

Subject to the Code of Federal Regulations, the shipper is responsible for the preparation of any hazardous material offered for transportation by water. The following certification will be shown on the shipping paper and signed by the shipper: "This is to certify that the above-named articles are properly classified, described, packaged, marked, and labeled and are in proper condition for transportation, according to the applicable regulations of the Department of Transportation."

2-4. Inspections and Acceptance

- a. Prior to commencement of the actual loading operation, all hatches and compartments in which military explosives cargo is to be carried will be thoroughly inspected by cargo operations personnel and qualified station inspectors. All defects and/or substandard conditions will be corrected prior to the loading operation in the affected hatch or compartment. A Coast Guard explosives loading detail (ELD) may be assigned to a vessel being worked at a Navy or Army depot, arsenal, ocean terminal, or other similar facility, unless the Commanding Officer of the facility declines the detail. However, staff directives or instructions issued by the individual Services can require mandatory acceptance of Coast Guard inspection details by the explosives terminal or station. When no Coast Guard ELD is assigned and in attendance, safe operations will be enforced by explosives-qualified inspectors from the port or station.
- b. As the loading of each compartment is completed, the adequacy and acceptance of the stowage will be approved by authorized station personnel and inspectors and by an authorized ship's officer. Final acceptance of completed cargo stowage will be certified by the ship's master or his authorized representative. A cargo stowage inspection record may be used for this purpose, a sample of which is shown in figure 2-1.

FINAL LOADE	HOLD INSPE D WITH MILI	CTION, ACCEPTAN TARY EXPLOSIVES	ICE AND CERTIFICATION AND HAZARDOUS MUNIT	OF SHIPS	
SHIP SS	American i	KNIGHT 3CT	VITY VANWPNSTAlcucae	PIER	BERTH 2
	TIME OF ARR	IVAL	DATE AND TIME LOADIN 0800 II AUG 7	STARTED DATE AND	TIME LOADING COMPLETED
10 30	14162 10	AUG /4	SHIP'S BLOCKE	SIGNATURES	STATION/COAST GUARD
DATE 11 AUG 74	1300	#1 3RD	BRACER SUPERVISOR	SHIP'S OFFICER	INSPECTOR
12	0900	ZND	Bul Smith	2 Jun Universit	Rulfiburger, USCG
12 AUG 74	1200	MAIN	Bull Smith	John Oludren y	Paullined
II AUG74	1500	#2 IN BOTTOM	E White	G. Jones 3/0	Paul Ward Dr. USCO
12 AUG14 12 AUG1	0930	3RD ZND	EMILES	Garnes 1/0	Haul abrid,
13 AUGN	0900	MAIN	Elitate	(2) Trace /2/1	Paul Ward
		/3			Tunt uxxxx
		#4			
			11		
IZAUG 74	1100	#5 ALANTOD	He frankly	6. Jones 2/11	Force Alams LTIS
13AU674 13AU674	1200	ZNO	Juney,	G. Jones 2/9	James Adams ITis
74AU674	0945	MAIN	li shuni W	G. Jones 2/2	James A dress the
13AUG 74	1115	#6 16' FLAT	BW5mith	Lan Contract	Paul Ward 15 usci
13 AU67Y 14 AU67Y	0830	26'FLAT 2ND	BUSMIT	John Broken	Haul Ward,
14 AUG74	1300	MNIN	Bullsmith	Samuel Marie	Paul Ward
		#7			
-		SPECIAL STON.		- 	
		SPECIAL STOW.	<u> </u>		
		SPECIAL STOW.			
		SPECIAL STOW.			
		SPECIAL STOW.			
HOLDS MARK	ED WITH AST	ERISK * CONTAIN	N SECURITY ITEMS	1	L
THE LOADIN	IG WAS CARRI	CER ED OUT IN ACCOR D AS SATISFACTO	RTIFICATION OF FINAL	TOARIE DECINATIONS	AND THE STOWAGE HAS BEEN
(SIGNATURE	1100	<u>u Parkin</u>	-	(SIGNATURE)	Wand LT USCG
(SIGNATURE BLOCKER	SHIP SUPER	Pillin		STATION/COAST	GUARD INSPECTOR
THE STOWAG	E HAS BEEN	INSPECTED BY ME	OR MY REPRESENTATIV	E AND IS ACCEPTED	AS SATISTACTORY. NO-
DATE	11/1/979	LFERAGE NOTED.		(SIGNATURE)	Hall and
	7				- X W

Figure 2-1 Typical cargo stowage inspection record.

Should a dispute arise about the adequacy of the stowage, the matter should be referred to the Military Sealift Command (MSC) representative, the MSC Office, or the MSC Area Commander as appropriate.

2-5. Standard Feedback Forms and Systems

Cargo stowage is inspected and the cargo condition reported during and upon completion of the voyage.

a. SF 364 (Report of Discrepancy) (fig 2-2) will be prepared by the military load inspector, Coast TM 55-607/NAVSEA OP 3221 Rev 2 Guard inspector, or ship's master to report unsatisfactory conditions noted in received cargo, including item damage or loss resulting from improper packaging. Any deficiency in packaging involving ammunition, explosives, and other hazardous materials must be reported, whether or not damage or other unsatisfactory condition has resulted. SF 364 must be filed in any instance of improper identification or marking of items, packages, containers, or unitized loads of ammunition, explosives, or hazardous materials. Joint Regulation AR 700-58/NAVSUPINST 4030-29/AFR 71-13/ MCO P4030.29A/DSAR 4145.8 prescribes use of SF Form 364 and provides instructions for preparing, routing, and taking corrective action.

STANDARD FORM 364 (REV. 2-80)
Prescribed by GSA FPMR 101-26.8

REPORT OF DISCREPANCY (R	OD)		1. D	ATE OF PREPA	ARATION	2. REPO	ORT NUMBE	R	
X SHIPPING	PACKAGING		(6 May 88					
3. TO (Name and address, include ZIP Code)			4. FI	ROM (Name an	d address,	include ZIP	Code)		
Chief, Storage Branch			Wa	ter Termi	nal Br	anch			
U. S. Army Garrison, Honsh	hu		U.	S. Army	Garris	on, Hon	shu		
APO Seattle 98764			AP	0 Seattle	9876	0			
5a.SHIPPER'S NAME Ordnance Ammo Depot Songhwan Ni, Korea			5b. NUMBER AND DATE OF NUMBER (GBL, Waybill, TCN, etc.) A33333				UMENT V, etc.)		
APO San Francisco 96271		···		1 May 88		AX3	8541		
7a. SHIPPER'S NUMBER (Purchase Order/Shipment, Contract, etc.)	OFFICE ADMINI	STERING (CONT	RACT		8. REQUIS sition, Purc	ITIONER'S 1 hase Request	NUMBER , etc.)	(Requi-
N/A	N/A					123x	x125		
9. SHIPMENT, BILLIN	NG, AND RECEIPT	DATA			10.	DISCREPA	NCY DATA		11.
NSN/PART NUMBER AND NOMENCLATURE	UNIT OF ISSUE	QUANT SHIPPE BILLE	D/	QUANTITY RECEIVED	QUAN- TITY	UNIT PRICE	TOTAL COST	CODE 1	AC- ² TION CODE
(a)	(b)	(c)		(d)	(a)	(b)	(c)	(d)	
1315-00-0279-CJ30	1	2		50	50	\$1.00	\$50.00	Z	D
		AMP	E						

12. REMARKS (Continue on separate sheet of paper if necessary)

7540-00-159-4442

364-103

Five pallets of propellant charge were found in damaged condition in Hatch No. 2 Lt of SS Green Lake during discharge operations at Hiro Port, Japan, on 7 Jul 87. Vessel sailed from Pusan, Korea. Damaged 5 pallets were delivered to storage branch, Dir. of Ammo., USAGH, on 8 Jul 87 via barge No. 74.

¹ DISCREPA	ANCY CODES	² ACTION CODES
CONDITION OF MATERIAL C1 — In condition other than that indicated on release/receipt document C2 — Expired shelf life C3 — Damaged parcel post shipment SUPPLY DOCUMENTATION D1 — Not received D2 — Illegible or mutilated D3 — Incomplete improper or without authority (Only when receipt cannot be properly processed) MISDIRECTED MATERIAL M1 — Addressed to wrong activity OVERAGE/DUPLICATE SHIPMENTS O1 — Quantity in excess of that or receipt document O2—Quantity in excess of that requested (Other than unit of issue pack) O3 — Quantity duplicates shipment PACKING DISCREPANCY P1 — Improper preservation P2 — Improper preservation P3 — Improper marking P4 — Improper unitization 13. FUNDING AND ACCOUNTING DATA N/A 14a. TYPED OR PRINTED NAME, TITLE, AND PHPARING OFFICIAL Mr. James Hoover, ITO 927-4646	PRODUCT QUALITY DEFICIENCIES Q1 —Deficient material (Applicable to Grant Aid and FMS shipments only) SHORTAGE OF MATERIAL S1 — Quantity less than that on receipt document S2 — Quantity less than that recuested (Other than unit of issue pack) S3 — Non-receipt of parcel post shipments ITEM TECHNICAL DATA MARKINGS (i.e., Name Plates, Log Books, Operating Handbooks, Special Instructions, etc.) T1 — Missing T2 — Illegible or mutilated T3 — Precautionary operational markings missing T4 — Inspection data missing or incomplete T5 — Serviceability operating data missing or incomplete T6 — Warranty data missing WRONG ITEM (Identify requested item as a separate copy in Item 9 aboue) W1 — Incorrect item received W2 — Unacceptable substitute OTHER DISCREPANCIES Z1 — See remarks	1A — Disposition instructions requested (Reply on reverse) 1B — Material being retained (See remarks) 1C — Supporting supply documentation requested 1D — Material still required expedite shipment (Not applicable to (FMS) 1E — Local purchase material to be returned at supplier's expense unless disposition instructions to the contrary are received within 15 days (Reply on reverse) (Not applicable to FMS) 1F — Replacement shipment requested (Not applicable to FMS) 1G — Reshipment not required. Item to be re-requisitioned. 1H — No action required. Information only
15. DISTRIBUTION ADDRES" EES FOR COPIES		
2 - Chief, Storage Br. USAGH		
1 - ORD Ammo Depot, Songhwan N	i, Korea	

Figure 2-2. Report of Discrepancy (ROD) (SF 364) (Sheet 1 of 2).

(Previous edition is obsolete.)

	16. FROM:	17. DISTRIBUTION	ADDRESSEES FOR CO	PIES	
	Same As #4	Same A	s #5		
	Same As #3		this documen address, incl starting one t the left dot. must NOT ex dot. Address	envelope to mail t. Insert name and uding ZIP Code, typing space below Each address line ttend beyond right must not exceed pace typing lines.	
	19. IN ACCORDANCE WITH NOTICE OF DI	SCREPANCY ON FA	ACE OF THIS FORM:		
Fold	a. MATERIAL DOCUMENT NUMBER HAS WILL SHIPPED AX38541	b. NO RECOR	OF SHIPMENT, RES	UBMIT REPORT TO PRIATE REGULATION.	
	AN ADJUSTMENT IN BILL- ING HAS BEENWILL BE C. PROCESSED AS A: CREDIT	d. MINVOICE/	BILL e. X Shipmen	OF DELIVERY (Parcel Post ts) OR EVIDENCE OF NT ENCLOSED.	
	AN ADJUSTMENT IN BILLING FOR THE SENTED DISCRI	EPANCY WILL NOT	BE PROCESSED FOR T	HE FOLLOWING REASON	
	(1) REASON FOR NOT PROCESSING	(2)	PRESCRIBING REGULATION		
	(a) DISCREPANCY WAS NOT REPORTED WITHIN THE TIME FRAMES ALLOWED AND/OR	(a) CHAPTER DEFICIENT OR BILLIN	5 OF THE GSA HANDB CIES IN GSA OR DOD S IGS (FPMR 101-26.8)	OOK. DISCREPANCIES OR HIPMENTS, MATERIAL,	
	(b) DOLLAR VALUE DOES NOT MEET THE CRITERIA PRE- SCRIBED IN THE REGULATION OR AGREEMENT INDI- CATED IN 191(2)	ND/OR 7 OF DOD 4000 ING SYSTEM (MILSBIL IR AND ACCEPTANCE,	.25-7-M, MILITARY STAND- LS) AND/OR DD 1513, U.S. AS APPLICABLE.		
	20. THE FOLLOWING DISPOSITION IS TO BE	MADE OF THE REF	ERENCED MATERIAL:	Indus	
	PROCESS FOR DISPOSAL IN ACCORDANCE b. X SION C	SENTATIVE WILL ONCERNING DISPO	CALL FOR DISCUS- SITION IN:	15	
	c. RETAIN MATERIAL AT NO CHARGE.	RIAL WILL BE PICK	ED UP IN:	DAYS	
Fold here	(2) CHARGES COLLECT-VIA: FREIGHT EXPR	ESS PARCEL	NOTE: Please et	ige advanced herewith · nclose postage. Material ed Parcel Post collect.)	
	f. OTHER (Specify)				
				DATE	
	21. IF MATERIAL IS STILL REQUIRED, 22. X MATE	ACEMENT WITH SA ERIAL WILL BE MA	TISFACTORY DE ON OR BEFORE:	15 May 88	
	23. REMARKS (Continue on separate sheet of paper if necessary) N/A				
				T	
	246. TYPED OR PRINTED NAME AND PHONE NUM- BER OF PREPARING OFFICIAL 24b. SIGNATUR	RE		24c. DATE	
	Mr. James Hoover, ITO 927-4646			1 May 88	
	U.S. GOVERNMENT PRINTING OFFICE: 1987-177-151		STANDARD F	ORM 364 BACK (REV. 2-80)	

Figure 2-2. Report of Discrepancy (ROD) (SF 364) (Sheet 2 of 2).

b. Details of improper loading, stowing, handling, blocking and bracing, and lashing are reported by the discharging activity on Standard Form 361 (Transportation Discrepancy Report) (fig 2-3). Joint Regulation AR 55-38/NAVSUPINST 4610.33A/AFM 75-18/MCO P4610.19B/DSAR 4500.15 provides details for preparation and disposition of the Standard Form 361.